


Bante 932 Benchtop Water Hardness Meter



Features

- 2 to 5 points calibration from low to high concentrations
- Selectable water hardness units, including mmol/L, mg/L, german degree(°dH), english degree(°e) and french degree(°f)
- Automatic temperature compensation ensures accurate readings over the entire range
- Auto-read function senses and locks the measurement endpoint
- Calibration due alarm reminds users to calibrate the meter regularly
- Setup menu allows setting the number of calibration points, stability criteria, etc.
- Reset function automatically restores all settings to the factory defaults
- Expanded memory stores or recalls up to 500 data sets
- USB communication interface enables easy data transfer to a PC
- DAS software is capable of receiving data, recording measurements at specified intervals, exporting data to Excel



Ordering Information

Bante932: Meter, water hardness electrode, temperature probe, standard solutions, ionic strength adjuster, electrode holder, power adapter

Specifications

	Model	Bante 932
Water Hardness	Range	0.05...200 mmol/L, 0...1122°dH, 0...2000°fH, 0...1404°e, 0...8020 mg/L (Ca ²⁺), 0...19999 mg/L (CaCO ₃), 0...11220 mg/L (CaO)
	Resolution	0.001, 0.01, 0.1, 1
	Accuracy	±1% F.S.
	Calibration	2...5 points (0.01, 0.1, 1, 10, 100 mmol/L)
Temperature	Range	0.0...105.0°C
	Resolution	0.1
	Accuracy	±0.5°C
	Offset Calibration	1 point, reading ±10°C
General	Temperature Compensation	0...50°C, manual or automatic
	Stability Criteria	Standard or strict
	Calibration Due Alarm	1 to 31 days or off
	Memory	500 data sets
	Communication Interface	USB
	Connector	BNC, 3.5 mm jack socket
	Display	Custom LCD (125×100 mm)
	Power Supply	5V DC power adapter
Dimensions	210(L)×188(W)×60(H) mm	
Weight	1.5 kg	